



JOD Machinery Co., Ltd.



63,5 mm x 136,525 mm x 41,275 mm NSK 639/632 tapered roller bearings

Bearing No. 639/632

639/632 Bearing 2D drawings and 3D CAD models

Dimensione	63.5x136.525x41.275 mm
Marchio	NSK
Diametro del foro	63,5 mm
Diametro esterno	136,525 mm
Larghezza	41,275 mm
d	63,5 mm
D	136,525 mm
T	41,275 mm
B	41,275 mm
C	31,75 mm
ra1 max.	3,3 mm
a	29,9 mm
r min.	3,5 mm
r1 min.	3,3 mm
Da	119 mm
db	76 mm
ra max.	3,5 mm
da	79 mm
Db	125 mm
Peso	2,81 Kg
Carico dinamico di base (C)	195 kN
Carico statico di base (C0)	263 kN
(Grease) Velocità di lubrificazione	2800 r/min
(Olio) Velocità di	3800 r/min



JOD Machinery Co., Ltd.

lubrificazione	
Fattore di calcolo (e)	0,36
Fattore di calcolo (Y0)	0,91
LangID	1
ALP23	0
esterno r	3.3
ALP22	8
D_	136.525
ALP21	27
SHOG_yobi	639R/632R
RAr	259.404
r interno	3.5
GRS rpm	2800
D_b	125
D_a	119
DE_	115.076
SLR	28
Prod_Type3	TRBSR_ID_A
BETA_	1
ALPHA_	13.567
SDM_	100.508
DA1	15.843
DA2	14.14
hidYobi	639/632
Y1	1.7
B_	41.275
Numero di giri dell'olio	3800
Tavolo nascosto	ecat_NSTPRI
Y0	0.91
ra interno	3.5
rb esterno	3.3
C0	263



JOD Machinery Co., Ltd.

CUP	1.04
e	0.36
DA_	14.996
BET21	3
BET22	30
BET23	0
Z_	18
C_	31.75
yobi	639/632
KBRG	3161
CONE	1.77
DI_	85.749